

控制器性能比较图

性能	DPS	DPS/A	MT	MTS	MPS	MCS	MSC
手动时序控制清灰	—	—	●	●	●	●	●
自动压差控制清灰	—	—	—	—	●	●	●
遥控转换手动/自动控制模式	—	—	—	—	—	●	—
吹净功能 (低压差启动)	—	—	—	—	●	●	●
吹净功能 (风机开关联动)	—	—	●	●	—	—	●
新除尘器预涂层功能	—	—	—	—	●	●	—
新除尘器最短清灰频率设定	—	—	—	—	—	●	—
破袋泄漏报警功能	—	—	—	—	—	—	—
破袋泄漏定位功能	—	—	—	—	—	—	—
破袋位置阀门隔离	—	—	—	—	—	—	—
脉冲间隔比例调节	—	—	—	—	—	—	—
4-20mA压差值变送输出	—	—	—	—	●	●	●
遥控暂停功能	—	—	●	●	●	●	●
远程控制清灰频率	—	—	—	—	—	—	—
主一副控制器扩展功能	—	—	—	—	—	—	●
自动跳过没有连接的阀门	—	—	●	●	●	●	●
数字显示屏	●	●	●	●	●	●	●
设定脉冲宽度	—	—	●	●	●	●	●
设定脉冲间隔	—	—	●	●	●	●	●
设定脉冲周期	—	—	—	—	—	●	—
设定吹净功能的脉冲间隔	—	—	●	●	●	●	●
设定吹净功能的周期次数	—	—	●	●	●	●	●
压差数字显示	●	●	—	—	●	●	●
压差上限报警	●	●	—	—	●	●	●
压差下限报警	—	—	—	—	—	—	●
电磁线圈故障报警	—	—	●	—	—	●	●
微处理故障报警	—	—	●	●	●	●	●
低压停机功能	—	—	—	—	—	—	●
运行时间累计	—	—	—	—	●	●	●
功能菜单设定方式	—	—	●	●	●	●	●
功能模块插入方式	—	—	—	—	—	—	—
供电电压	110/220VAC (±10%)	110/220VAC (±10%)	115/230VAC (±15%)	24/115/230VAC (±20%)	24/115/230VAC (±20%)	115/230VAC (±10%)	115/230VAC (±10%)
			特殊: 24/48VAC 或24VDC			特殊: 24/48V AC 或24V DC	
输出电压	—	—	24/115/230V AC 特殊: 48V AC 或24/48V DC	24/115/230V AC	24/115/230V AC	24/115/230V AC	24V DC
压差显示范围	0~3 kPa	0~3 kPa	—	—	0.01~2.50kPa	0.01~9.99kPa	0.01~9.99kPa
输出端子数量	—	—	4~32	4~16	4~16	4~128	10~200

注: “●”表示具有此功能; “—”表示没有此功能。

澳大利亚高原控制有限公司上海代表处



Tel 电话:86 21 52398810

Fax 传真:86 21 52398812

GOYEN CONTROLS CO. PTY. LTD. • ABN 60000168098 www.cleanairsystems.com

REPRESENTED IN • AUSTRALIA • NEW ZEALAND • NORTH EAST ASIA • SOUTH EAST ASIA • USA • EUROPE